

IN THE CLAIMS

✓ ✓ ✓ ✓  
Please amend claims 1 and 4-7 by rewriting the same to the following:

*Sub B1*  
1. (Amended) A receiver for receiving television broadcast and for synthesizing plural received images, comprising:  
a reception antenna for receiving television broadcast;  
display data outputting means for outputting the received television broadcast to a picture display device;  
*A1 cancel*  
a data memory for transiently storing data from the received television broadcast representative of only one image, in which said one image is the same as that currently displayed by said picture display device;  
printing command inputting means for inputting a command for printing a desired image selected from the images displayed on said picture display device;  
printing command outputting means for reading out the desired image from the data memory to a printing device; and  
picture data synthesis means for synthesizing the received television broadcast with the desired image, thereby generating synthesized image data for display on the picture display device.

*A2 cancel*  
4. (Amended) A picture data processing method comprising the steps of:  
receiving television broadcast;  
outputting the received television broadcast to a picture display device;

transiently storing data from the received television broadcast representative of only one image, in which said one image is the same as that currently displayed by said picture display device;

inputting a command for printing a desired image selected from the images displayed on said picture display device;

reading out the desired image from the data memory to a printing device; and

*A2  
cancel.*  
synthesizing the received television broadcast with the desired image, thereby generating synthesized image data for display on the picture display device.

5. (Amended) The picture data processing method according to claim 4 wherein the step of synthesizing the received television broadcast with the desired image is terminated when said printing device prints the desired image.

6. (Amended) The picture data processing method according to claim 4 wherein the step of synthesizing the received television broadcast with the desired image is terminated when a command for terminating the display of the synthesized image data is inputted.

7. (Amended) The picture data processing method according to claim 4 wherein the step of synthesizing the received television broadcast with the desired image is terminated when a pre-set time has elapsed

---